



HIGH-SPEED INDUSTRIAL MASS ROLL TO ROLL PRINTER 10.5'



| PRINTHEAD | HIGH SPEED MODE | STANDARD MODE | HIGH QUALITY MODE | INK COLOR |
|----------------------|--|--|---|-----------|
| KM1024i-30PL 8 Heads | 480x360 dpi 1pass 5166 ft ² /h (480 m ² /h) | 480x720 dpi 2pass 2798 ft ² /h (260 m ² /h) | 480x1080 dpi 3pass 1872 ft ² /h (174 m ² /h) | KCMY |
| KM1024i-30PL 4 Heads | 480x360 dpi 1pass 2583 ft ² /h (240 m ² /h) | 480x720 dpi 2pass 1399 ft ² /h (130 m ² /h) | 480x1080 dpi 3pass 861 ft ² /h (80 m ² /h) | KCMY |
| KM512i-30PL 8 Heads | 480x360 dpi 2pass 2475 ft ² /h (230 m ² /h) | 480x720 dpi 3pass 1722 ft ² /h (160 m ² /h) | 480x1080 dpi 4pass 1291 ft ² /h (120 m ² /h) | KCMY |
| KM1024i-13PL 8 Heads | 540x360 dpi 2pass 2368 ft ² /h (220 m ² /h) | 540x720 dpi 3pass 1614 ft ² /h (150 m ² /h) | 540x1080 dpi 4pass 1291 ft ² /h (120 m ² /h) | KCMY |
| KM512i-30PL | 480x360 dpi 2pass 1184 ft ² /h (110 m ² /h) | 480x720 dpi 3pass 861 ft ² /h (80 m ² /h) | 480x1080 dpi 4pass 645 ft ² /h (60 m ² /h) | KCMY |



KM1024i PrinterHead



KM512 PrinterHead

TECHNICAL PARAMETERS

| | |
|-----------------------------------|--|
| Print technology | Industrial Piezoelectric Inkjet |
| Ink Types | Solvent ink |
| RIP Software | Photoprint, Maintop |
| Color configuration | 4Color |
| Operating system | Win 7/10 64bits |
| Image format | TIFF/JPEG/EPS/PDF |
| Print head height | 0.3in (8mm) above media adjustable |
| Media type | Vinyl, flex, polyester, Back lit film, window film, etc. |
| Printing Width | 10.5 ft (3,200mm) |
| Data interface | Hi-Speed USB 2.0 |
| Maximum power | 3.5KW |
| Access Parameter | AC220V (+-5%) 50HZ/60HZ |
| Humidity | 40-60% RH (no condensing) |
| Temperature | 20-28°C (77 - 90° F) |
| MacVThine dimension/Weight | L16.4 x W4 x H5 ft / 1763 lb L5,000 X W1,230 X H1,530mm / 800Kg |
| Package Dimension /Weight | L16.7 x W3.5 x H5.5 ft / 1984 lb L5,100 X W1,080 X H1,680mm / 900Kg |