

\$35,000 USD



**ROTARY
ATTACHED**



PRACTICAL FORMAT UV PRINTER 3'X2'

Take advantage of full bleed 3x2ft (90cmx60cm).
With integrated measuring tape to the length and width of the table



RICOH GEN5i PRINT HEAD

3 Print heads included
CMYK W V




AUTOMATIC HEIGHT SYSTEM

Print height: 33.4" (2-850mm)
Adjustable



HIGH QUALITY UV INKS

Our UV inks allow great adhesion and magnificent color quality



VACUUM TABLE

High absorption in the entire table area to flatten materials and avoid collisions



PRINT WITHOUT LIMITS:

Wood, Glass, Yard signs, Acrylic, doormats,
Metal, Canvas **AND MANY MORE**



PRINTHEAD	HIGH SPEED MODE	STANDARD MODE	HIGH QUALITY MODE	INK COLOR
RICOH G5i-3.5PL	720x600dpi 4pass 80.7ft ² /h (7.5m ² /h)	720x900dpi 6pass 60.2ft ² /h (5.6m ² /h)	720X1200dpi 8pass 41ft ² /h (3.8m ² /h)	KCMY W V
RICOH G5i-3.5PL	720x600dpi 4pass 140ft ² /h (13m ² /h)	720x900dpi 6pass 86ft ² /h (8m ² /h)	720X1200dpi 8pass 64.5ft ² /h (6m ² /h)	KCMY W
RICOH G5i-3.5PL ¾ Heads	720x600dpi 4pass 150ft ² /h (14m ² /h)	720x900dpi 6pass 107ft ² /h (10m ² /h)	720X1200dpi 8pass 64.5ft ² /h (6m ² /h)	KCMY W

TECHNICAL PARAMETERS	
Print technology	Industrial piezoelectric inkjet
Ink Types	Environmental protective UV ink
RIP Software	Photoprint, Maintop, Printer factory
Color configuration	4Color/6Color/White
Operating system	Win 7/10 64bits
Image format	TIFF/JPEG/EPS/PDF
Print head height	33.4" (2-850mm) above media adjustable
Media type	Wood, aluminum, doormats, door plank paperboard, PVC, expansion sheet, ceiling panel, glass ceramics, acrylic, etc.
Print Head	3 RICOH GEN5i included
Printing Width	Panel: 900mm (3ft)(Width) x 600(2ft)(Depth)mm
Maximum weight of material	30lb/ft (45kg/m)
UV Curing Lamp	LED Water cooling system
Maximum power	15A ; 3.5KW
Access Parameter	AC220V (+-5%) 50HZ/60HZ
Humidity	35-80% RH (no condensing)
Temperature	25-32 C (77 to 90 F)
Machine dimension/Weight	93" x 46" x 53" 881lb
Package Dimension /Weight	97" x 55" x 42" 992lb

