

HIGH PRECISION PHOTO MACHINE ROLL TO ROLL PRINTER 6.0'



PRINTHEAD	HIGH SPEED MODE	STANDARD MODE	HIGH QUALITY MODE	INK COLOR
EPSON i3200 (2 Heads)	360x1800dpi 4pass 473ft2/m (44m2/h)	720x1200dpi 6pass 344ft2/m (32m2/h)	720x1800dpi 8pass 236ft2/m (22m2/h)	2x KCMY
EPSON XP600 (2 Heads)	720x720dpi 4pass 258ft2/m (24m2/h)	720x1080dpi 6pass 182ft2/m (17m2/h)	720x1440dpi 8pass 140ft2/m (13m2/h)	2x KCMY
EPSON DX5	720x720dpi 4pass 322ft2/m (30m2/h)	720x1080dpi 6pass 215ft2/m (20m2/h)	720x1440dpi 8pass 107ft2/m (10m2/h)	2x KCMY



EPSON i3200PrinterHead



EPSON XP600 PrinterHead



EPSON DX5 PrinterHead

TECHNICAL PARAMETERS

Print technology	Micro piezoelectric inkjet
Ink Types	Eco-solvent ink, water ink
RIP Software	Photoprint, Maintop
Color configuration	4Color
Operating system	Win 7/10 64bits
Image format	TIFF/JPEG/EPS/PDF
Print head height	0.3in (8mm) above media adjustable
Media type	PP sythentic paper, vinyl sheet, film, coated paper, acid proof paper banner, canvas, adhesive, banner, etc.
Printing Width	6.0 ft (1800mm))
Heating and Drying System:	Equipped Infrared Ray + Fan
Data interface	Hi-Speed USB 2.0
Maximum power	> 15A ; 2.5KW
Access Parameter	AC220V (+-5%) 50HZ/60HZ
Humidity	35-80% RH (no condensing)
Temperature	15-32C (59 to 90F)
MacVThine dimension/Weight	T 5.9 L9.7 x W2.5 x H5.2 ft / 529 lb T 1,802 L2,980 X W790 X H1,590mm / 240Kg
Package Dimension /Weight	T 5.9 L11 x W2.4 x H2.5 ft / 705 lb T1,802 L3,350 X W740 X H770mm / 320Kg