

**PRINTS ON FLAT
AND CYLINDRICAL
RIGID MATERIALS**



PRACTICAL FORMAT UV PRINTER 3'X2'

Take advantage of full bleed 3x2ft (90cmx60cm).
With integrated measuring tape to the length and
width of the table



TOSHIBA CE4 PRINthead

4 Toshiba CE4 print heads included
CMYK LC LM W




AUTOMATIC HEIGHT SYSTEM

Print height: 3 1/4" (80mm)
Adjustable



HIGH QUALITY UV INKS

Our UV inks allow great adhesion and
magnificent color quality



VACUUM TABLE

High absorption in the entire table area to
flatten materials and avoid collisions

PRINT WITHOUT LIMITS:

Wood, Glass, Yard signs, Acrylic, doormats,
Metal, Canvas **AND MANY MORE**



PRINTHEAD	HIGH SPEED MODE	STANDARD MODE	HIGH QUALITY MODE	INK COLOR
TOSHIBA CE4 4 HEADS	600x900dpi 4pass 79ft2/m (7.4m2/h)	600x1200dpi 6pass 73ft2/m (6.8m2/h)	600X1800dpi 8pass 47ft2/m (4.4m2/h)	KCMY Lc Lm W
TOSHIBA CE4 5 HEADS	600x900dpi 4pass 79ft2/m (7.4m2/h)	600x1200dpi 6pass 73ft2/m (6.8m2/h)	600X1800dpi 8pass 47ft2/m (4.4m2/h)	KCMY Lc Lm W V

TECHNICAL PARAMETERS	
Print technology	Industrial piezoelectric inkjet
Ink Types	Environmental protective UV ink
RIP Software	Photoprint, Maintop, Printer factory
Color configuration	4Color/6Color/White
Operating system	Win 7/10 64bits
Image format	TIFF/JPEG/EPS/PDF
Print head height	2-80mm above media adjustable
Media type	Wood, aluminum, doormats, door plank paperboard, PVC, expansion sheet, ceiling panel, glass ceramics, acrylic, etc.
Print Head	4pcs Toshiba CE4
Printing Width	Panel: 900mm (3ft)(Width) x 600(2ft)(Depth)mm
Maximum weight of material	30lb/ft (45kg/m)
UV Curing Lamp	LED Water cooling system
Data interface	Hi-Speed USB 2.0 / 3.0
Maximum power	20A ; 2.5KW
Access Parameter	AC220V (+-5%) 50HZ/60HZ
Humidity	35-80% RH (no condensing)
Temperature	15-32C (59 to 90F)
Machine dimension /Weight	77" x 41" x 43" 661lb
Package Dimension /Weight	89" x 51" x 41" 837lb

